LD.SPEC.0709 Last Printed: 7/17/2009 9:05 AM



Rasmussen Iron Works, Inc

info@rasmussen.biz

12028 E. PHILADELPHIA ST. WHITTIER, CA 90601 U.S.A. (562) 696-8718 FAX: (562) 698-3510 www.rasmussen.biz

LD Multi-Burner



The LD Hearth Kits are designed specifically for use with the larger Timberfire (PH) logs. Custom log stacks may also be created for use on these systems. It is available in the following sizes:

LOG SET SIZE	HEIGHT	DEPTH	REAR WIDTH	FRONT WIDTH	GAS PIPING INSIDE DIAM.	CHIMNEY AREA
30 INCH	26	20	30	38	1/2"	12" DIAM.
36 INCH	30	22	36	44	1/2"	14" DIAM.
42 INCH	30	22	42	50	1/2"	14" DIAM.
48 INCH	34	22	48	58	3/4"	16" DIAM.
54 INCH	34	22	54	64	3/4"	16" DIAM.
60 INCH	34	22	60	70	1"	18" DIAM.
66 INCH	34	22	66	76	1"	18" DIAM.

The LD Burners are constructed of heavy 16-guage steel, with 1/2" schedule-40 pipe (not light duty tubing) for the main burner tube, and 1/4" steel tubing for the ember booster portions of the burner. All seams are welded for maximum performance and durability. LD burners include; 5/8" Grate, Sand (Natural Gas pan filler), Volcanic Ash (Natural Gas decoration or Propane pan filler), Ember Magic, Connector Kit, Damper Clamp and Instructions.