

TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No: MERB00000EV Revision No:

This Certificate is issued by DNV UK Limited based on authorisation of the Maritime & Coast Guard Agency (MCA) as an UK Approved Body to undertake conformity assessments on marine equipment in accordance with the requirements of the Merchant Shipping (Marine Equipment) Regulations 2016 as amended.

This is to certify:

That the Universal automatic identification system (AIS)

with type designation(s) FA-170

Issued to

Furuno Electric Co., Ltd.

Nishinomiya, Japan

is found to comply with the requirements in the following Regulations/Standards: Regulation MSN 1874 Amendment 6,

item No. UK/4.32. SOLAS 74 as amended, Regulations V/18, V/19 & X/3, IMO Res. A.694(17), IMO Res. MSC.36(63), IMO Res. MSC.97(73), IMO Res.MSC.302(87), IMO Res. MSC.191(79), ITU-RM-1371-5 (02-2014), IMO Res.MSC.74(69)

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until 2026-01-18.

Issued at London on 2022-12-28

DNV local unit: Kobe

Approval Engineer: Frederik tore Elter

Approved Body No.: 0097

for DNV UK Ltd.

Christine Mydlak-Röder **MER Service Responsible**



by the MCA

issued when the production-control phase module (D, E or F) of Schedule 2 of the Merchant Shipping (Marine Equipment) Regulations 2016, as amended is fully complied with and controlled by a written inspection agreement with an approved body. The product liability rests with the manufacturer or his representative in accordance with the Merchant Shipping (Marine Equipment) Regulations 2016. This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV UK Ltd. of any

changes to the approved equipment. Should the specified regulations or standards be amended during the validity of this certificate, UK Approved Body Authorised the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply. This certificate remains valid unless suspended, withdrawn, re-called, or cancelled,

The Mark of Conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: MER 201.GBR Revision: 2022-09 Page 1 of 5 www.dnv.com



Revision No: 0

Product description

The FA-170 UAIS consists of the following units:

| Component | Location |
|------------------|-----------|
| AIS transponder | Protected |
| MKD | Protected |
| Power supply | Protected |
| GPS/GNSS antenna | Exposed |
| VHF antenna | Exposed |

For details, see Appendix.

Application/Limitation

The internal GPS/GLONASS (GNSS) sensor of FA-170 may be used as back-up sensor for position reporting for the transmitted AIS messages.

The FA-170 components shall be installed in compliance with the Installation Manual Pub. No. IME44900F22 (or later revisions).

Type Examination documentation

• For details, see Appendix.

Tests carried out

- IEC 61993-2 (2018)
- IEC 61108-1 (2003)¹⁾
- IEC 61108-2 (1998)¹⁾
- IEC 61162-1 (2016)
- IEC 61162-2 (1998)
- IEC 61162-450 (2018)
- IEC 62288 (2014)
- IEC 60945 (2002) incl. Corr.1 (2008)
- IEC 62923-1 (2018) and IEC 62923-2 (2018)
- CCNR Test standard Inland AIS Ed.2.0 (2012)

Marking of product

The type designation and name and contact address of the manufacturer shall be affixed visibly, legibly and indelibly to the product. In addition the product shall be marked with serial number, safe distance to magnetic compass, power consumption and/or supply voltage.

Form code: MER 201.GBR Revision: 2022-09 www.dnv.com Page 2 of 5

¹⁾ as applicable for position reporting



Revision No: 0

APPENDIX

Product description

The FA-170 UAIS comprises combinations of the following components:

| Unit | Model Name | Remark | |
|-------------------------------|-----------------------------|-----------------------------------------------------|--|
| Transponder unit | FA-1701 | | |
| Interfaces | External displays | 2 COM ports | |
| | Pilot plug | 4 COM ports | |
| | Sensors | 3 serial ports (IEC61162-1) | |
| | LAN | 1 RJ45 port (CAT5 STP) | |
| | External alarm I/O | | |
| Monitor unit (MKD) | FA-1702 | | |
| GPS/VHF combined antenna and | GVA-100* | *May be exchanged with GPA-017S and separate VHF | |
| distributor unit, or; | and DB-1 | whip antenna | |
| GPS antenna and separate | GPA-017S** | **FAB-151D or analogous antenna as specified in the | |
| VHF antenna, or; | | installation manual | |
| GNSS/VHF combined antenna and | GVA-170 * | *May be exchanged with GPA-017S and separate VHF | |
| distributor unit, or; | and DB-1 | whip antenna | |
| GNSS antenna and separate | GPA-022S** | **FAB-151D or analogous antenna as specified in the | |
| VHF antenna | | installation manual | |
| Software | 0550255-02.xx ¹⁾ | ¹⁾ FA-1701 | |
| | 0550256-02.xx ²⁾ | ²⁾ FA-1702 | |
| | 48504650xx ³⁾ | ³⁾ GPS receiver | |

Optional components:

| Pilot plug | FA-1703 | Flush mounting panel |
|--------------------|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| VHF whip antenna | FAB-151D | May be included in GVA-100 / GVA-170 or combined with GPA-017S / GPA-022S or replaced by an analogous antenna as specified in the installation manual |
| AC/DC power supply | PR-240 or, PR-241 | |

Type Examination documentation

| DNV No | Document ID | Rev | Description |
|-----------|-----------------------|-----|----------------------------------------------------------------|
| 6 | K20-17-815 | | DNV type approval testing report (GP-170 GPS receiver) |
| 11 | K05-17-833 | | DNV Type approval Testing Report - Class A AIS". |
| 12 | K05-17-848 | | DNV Type Approval Testing Report - Physical test |
| 13 | K05-17-845 | | DNV Type Approval Testing Report - IEC61162-1/2/450 FA-170 |
| 14 | FLI-12-11-129 | | Test Report - IEC61162-1 UAIS transponder FA-150 |
| 15 | BSH/4612/4322181/12-4 | | Conformance Test Report - AIS class A, FA-150 IEC61162-1 |
| 16 | FLI-12-15-034 | | Test Report - IEC61162-450 UAIS transponder FA-170 |
| 17 | FLI-12-15-033 | | Test Report - IEC61162-1/-2 UAIS transponder FA-170 |
| 18 | K05-17-834 | | DNV Type Approval Testing Report - Internal GPS- FA-170 |
| 19 | FLI-12-15-035 | | Test Report - IEC62288 - UAIS transponder FA-170 |
| 20 | FLI-12-15-032 | | Test Report - IEC60945 clause 12.2 - radio frequency radiation |
| 21 | FLI-12-15-031 | | Test Report - IEC60945 - compass safe distance |
| 22 | FLI-12-15-030 | | Test Report - IEC60945 - environmental + misc. |

Form code: MER 201.GBR Revision: 2022-09 www.dnv.com Page 3 of 5



Revision No: 0

| DNV No | Document ID | Rev | Description |
|-----------|---------------|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 23 | FLI-12-15-029 | | Test Report - IEC60945 - EMC |
| 28 | K05-17-880 | | FA-170 DNV type approval testing report IEC61993-2 |
| 30 | K05-17-831 | | FA-170 DNV Type Approval testing report (CCNR inland AIS) |
| 34 | FLI12-02-001 | | FA-100 IEC60945 test report |
| 35 | FLI12-04-049 | | FA-150 IEC60945 test report |
| 36 | FLI12-04-057 | | PR240 IEC60945 test report |
| 38 | LIC 12-19-022 | | FA-170 IEC61162-1(Ed.5) Test report |
| 39 | K05-17-1052 | | FA-170: IEC61162-1 Ed.5 type approval testing report |
| 40 | K05-17-832 | | DNV type approval testing report BAM MSC.302(87) |
| 44 | K05-17-1095 | 2020/11/24 | Report: Furuno - FA-170 Test report for DNV (IEC 62923-1-2 Ed1) |
| 58 | LIC 12-20-158 | 20 October 2020 | Report: LABOTECH, IEC 61162-450 - Model: U-AIS TRANSPONDER Type: FA-170 |
| 60 | K05-17-1096 | 2020/11/27 | Report: Furuno - IEC 61993-2 - DNV type approval testing report - Model: Class A shipborne equipment of the automatic identification System (AIS) Type: FA-170 |
| 61 | K05-17-1097 | 2020/11/24 | Report: Furuno FA-170 Test report for IEC 61108-2 Ed1 GPS/GLONASS antenna |
| 62 | LIC 12-20-174 | 13 Nov. 2020 | Report: LABOTECH IEC60945 - EMC Emissions - GVA-170 GNSS Antenna Model: U-AIS TRANSPONDER Type: FA-170 |
| 63 | LIC 12-20-175 | 13 Nov. 2020 | Report: LABOTECH IEC60945 - EMC Immunity - GVA-170 GNSS Antenna Model: U-AIS TRANSPONDER Type: FA-170 |
| 64 | LIC 12-20-178 | 30 Nov. 2020 | Report: LABOTECH IEC60945 - Vibration - GVA-170 GNSS Antenna Model: U-AIS TRANSPONDER Type: FA-170 |
| 67 | K20-17-1591 | 10 Mar. 2020 | Report: IEC61108-2 5.6.4.2 Testing Report of Angular antenna movement GLONASS (reference doc. K05-17-1097) |
| 68 | K20-17-1593 | 10 Mar. 2020 | Report: IEC61108-2 5.6.4.2 Testing Report of Angular antenna movement Differential GLONASS (reference doc. K05-17-1097) |
| 69 | K20-17-1600 | 10 Mar. 2020 | Report: IEC61108-2 5.6.5.3 Acquisition Interruption of GLONASS signals (reference doc. K05-17-1097) |
| 70 | K20-17-1570 | 12 Mar. 2020 | Report: Marine radio beacon receiver GPS/GLONASS/DGPS/DGLONASS (reference doc. K05-17-1097) |
| 71 | LIC12-20-018 | | Report: LABOTECH IEC 60945 (CSD) GPA-022S (reference doc. K05-17-1097) |
| 72 | LIC12-20-019 | | Report: LABOTECH IEC 60945 (EMC) GPA-022S (reference doc. K05-17-1097) |
| 73 | LIC12-20-025 | | Report: LABOTECH IEC 60945 (ENV) GPA-022S (reference doc. K05-17-1097) |
| 74 | OME44900E22 | E22: JAN. 8,2021 | Manual: Operators Manual - Class A AIS - Model: FA-170 |
| 75 | IME44900F22 | F22: JAN. 8, 2021 | Manual: Installation Manual - Class A AIS - Model: FA-170 |
| 76 | C82-02001-Z11 | Z11: OCT. 2020 | Manual: Installation Guide AC/DC POWER SUPPLY UNIT - Model PR-241 |
| 77 | LIC 12-20-120 | Rev. 1 | Report: LABOTEC IEC60945 ENV - Furuno AC/DC POWER SUPPLY UNIT Type: PR-241 |
| 78 | LIC 12-20-119 | Rev. 1 | Report: LABOTEC IEC60945 Compass safe distance - Furuno AC/DC POWER SUPPLY UNIT Type: PR-241 |
| 79 | LIC 12-20-120 | Rev. 1 | Report: LABOTEC IEC60945 EMC - Furuno AC/DC POWER SUPPLY UNIT Type: PR-241 |

Form code: MER 201.GBR Revision: 2022-09 www.dnv.com Page 4 of 5



Revision No: 0

| DNV No | Document ID | Rev | Description |
|-----------|---------------|--------|--------------------------------------------------------------------------------------------------------------------------------|
| 80 | LIC 12-20-122 | Rev. 1 | Report: LABOTEC IEC60945 excessive conditions, acoustic noise, dangerous voltage - Furuno AC/DC POWER SUPPLY UNIT Type: PR-241 |

Form code: MER 201.GBR Revision: 2022-09 www.dnv.com Page 5 of 5